

Shouson Theatre Venue Specifications (updated Jan 2024)



Shouson Theatre is the largest venue in HKAC with capacity 394 seats. The proscenium theatre offers superb views from every seat, which audiences can enjoy an intimate theatrical experience. It is primarily used for concert, drama and dance performances, but also ideal for film screenings and seminars.

DROP OFF AREA



Drop off area 1 Drop off area 2 Nearby Public Carpark Hong Kong Arts Centre Fenwick Street entrance The Harbourview Hotel entrance (No. 4 Harbour Road) Shui On Centre (No. 6-8 Harbour Road), Wanchai Towers (No. 12 Harbour Road) HKCEC Convention Plaza (No. 1 Harbour Road)



LOADING

Loading dock Height restriction of loading dock Scenery dock G/F entrance in Fenwick Street (opposite to HKAPA) 3m H Stage Left, size: 3.6W x 3.9D x 2.8H m Equipped with hoisting cargo cage for delivering goods from G/F loading dock to stage Maximum loading of Cargo Cage: 800Kg Shutter size: Stage level 2.8H x 3.7W m Ground level 2.1H x 2.6W m

AUDITORIUM

Continental style in Stall and Circle, entrances to auditorium at G/F, 1/F & 3/F	
Full Seating Capacity	394 (Stall 260, Circle 134)
Seating for Film show	380 (Stall 246, Circle 134)
Wheelchair space	1 at Stall seat G1

<u>STAGE</u>

Proscenium

Structural opening	8.08W x 5.49H m
Adjustable Width	8.08m to 11.5.m

Stage Floor

- Flat black surface hardboard (No painting or drilling)
- Harlequin Standfast black mat for dance flooring (Please allow time for setup during the booking time)

726Kg /m² (150 lbs. /sq. ft.)
Detail refers to "Technical Plan III"
2.5m
8.08m
11.45m
6.45m
0.55m
2.1m
14.8m
13.6m (Except Line 5, 16, & 24, which is 8m)
1m above auditorium floor

Hong Kong Arts Centre	
Forestage Forestage area can be lowered to auditorium level In the shape of trapezoid, size: 7.8W x 1.59D m	
Stage width can be extended to 10.5m by adding 2 rema Orchestra pit	ovable platforms
Forestage can be lowered beneath the auditorium level of Size: 7.8W x 3D x 1.7H m Accommodate up to 15 musicians	as orchestra pit
Rear Stage	16.25W x 2.5D m
Rear of Cyclorama (Crossover from stage left to right) Side Stage / Storage space	16.23W X 2.3D 11
Limited wing spaces on both sides (when main stage widt	h is 8 08m)
Stage Left	2W x 4.8D x 2.45H m
Stage Right	1.8W x 4.8D x 2.4H m
Stage Drapery	
Red Velour House Curtain (9W x 6.5H m)	1 flat (Electrically opened or raised manually)
Black border (10W x 2.5H m)	3 flats
Side masking flat (1.2W x 5.5H m)	10 flats
Black Mid Curtain(6.5W x 6.5H m)	1 Pairs
Side masking leg (2.5W x 6.5H m)	1 pairs
Black gauze (11W x 7H m)	1 flat
White gauze (11W x 7H m)	1 flat
Curved black backdrop (12W x 6H m)	1 flat
Curved white cyclorama (12W x 6H m)	1 flat
Flying System	
24 Manual rope-operated double purchase counterweigt	nt lines
Loading capacity	250Kg each
Barlength	Variable from 8.5m to 11m
Bar height	13.6m (Except Line 5, 16, & 24, which is 8m)
Bar diameter	48.5mm
Bar distance	0.2m (in general)
Header	Line 1
House curtain	Line 2
Film screen	Line 4
Resident spotbar	Line 5, 16 & 24
Black backdrop	Line 28
White cyclorama	Line 29



Motorized Winch Bar (Located at rear of cyclorama)	2
Bar length	6.8m (Up stage) 7.3m (Down stage)
Bar height	5.7m
Loading capacity	100Kg each
Other equipment	
Genie® AWP®-25S Super Series aerial work platform	Max. 5.9m H
	(operated by competent person and prior
	approved by Technical Department only)
Yamaha C2 baby grand piano	1
Yamaha upright piano	1
Black music stand #	28
Music stand light #	28
Podium	1
Table (1.8m L x 0.6m D x 0.7m H) #	4
Chair (Black with silver edge) #	40
Red Velour table cloths #	4

<u>LIGHTING</u>

Control Board	Located in lighting control room at rear of auditorium
	ETC Element 2
, with full back up control facilities, controllable of 140 channels	
	Control patching arrangement at switchboard
Dimmers	136 x 2kW production lighting dimmers and 4 x 5kW dimmers
Circuits	140 circuits
Power supply	13A wall-mounted socket outlets to UK standard are provided on the
	stage wall
Additional power st	One 60A x 3 phase socket, located at stage left loading bay
	The hirer may bring-in electrical equipment and connect to the additional
	power source, and the required electrical works must be conducted by
	the local registered electrical workers.
Lighting positions	2 light bridges over auditorium
	3 spot bars at Line 5, 16 & 24
	Light track at circle front



Houselight	Dimmer controlled. Take-control available in lighting control room		
Cyclorama light	Altman Spectra Series LED Cyclorama 5		5
Lighting equipment	Profiles Altman Ellipsoidals		
		PHX Zoom 750W 30/55°	24
		Altman Ellipsoidals	
		PHX Zoom 750W 15/35°	34
		ETC Source Four 750W 25/50°	4
		ETC Source Four 750W 15/30°	14
	Fresnel	Robert Juliat Lutin 306LF 1kW	20
		Robert Juliat 329HF 2kW	8
	Follow Spots	Robert Juliat Mannon 1.2kW MSD	2
	Others	ETC ColorSource PAR (RGB lime)	10
		Par-can 1kW	12
Other equipment	Light tower (ETC Source Four jr Zoom 575W 25/50°) 6		6
& Effect accessories	Light ladder		2 on each side
	Strobe light		1
	UV set		2
	Smoke gener	ator (Smoke Factory)	1
	Dry-ice gener	rator *	2
	Animation dis	С	2
	Gobo rotator& holder (fit for M & B size)		2
	LEE filters. Rar	nge L101-L206	
SOUND			
Control Room	Located in lighting control room at rear of auditorium		
Console	Yamaha IM8 - 40 channels, 8 group output		
Signal Processor	Yamaha Q20	31 equalizer	2
	Yamaha SPX-	990 effect processor	1
House Speaker System	Clair Brothers	Kit 12	2
	Clair Brothers	CS18-M subwoofer	2
Fixed House PA System	Clair Brothers FF2-H for stall & circle 4		
Mobile Speakers	Mackie C200/C300z Two-way loudspeaker 4		
Playback equipment	Tascam CD-1	60 CD player	1
	Tascam MD 3	50 Mini Disc player	1



Microphones	Shure SM 57	6
	Shure SM 58	6
	Crown PCC-160	3
Wirelesss Microphones	* Shure SLX4 Series	
	Handheld (SM 58 Head)	6
	Belt Pack	5
	Maximum 6 wireless mics in u	se
Communication system	Prompt corner at stage left, v	with stage manager's desk, talkback
	system, cue light system, cas	t call paging system to dressing rooms
	and infrared CCTV monitor v	iewing stage
	Wired intercom system availd	able at all control points
PROJECTION		
Screen	White perforated screen with	n adjustable masking
Sound (for 35mm Scree	ning) Dolby A/SR with surround sou	und system
Video/Computer Projec	tion SANYO PLC-XF70 (9000 lumer	ns) video projector *
	Computer Resolution: up to 1	1024 x 768
	Hirer should bring their own p	olayback device, e.g.: DVD player,
	Blu-ray Disc Player or Compu	ter
	Support Video Interface: Cor	mponent Video, VGA, HDMI, DVI
35mm Projection	Century projector 3KW xenor	n lamphouse x 2
	Cinemascope: approx.7.9W	x 3H m
	Standard: approx. 4.7W x 3.6	Hm

DRESSING ROOM & OTHER FACILITIES

Dressing room	6 dressing rooms (Room A-E & H) at G/F level
	Room A-C & H for 3 - 4 person and Room D & E for 6 - 8 person,
	Both sides of stage have staircase access to dressing room
	Show relay and cast paging in the area of backstage and
	dressing room
	All rooms equipped with access codes locks and lockers
	Lockers in the dressing rooms are fitted with a staple and hasp
	In order to lock a locker, hirer should bring their own padlocks
Quick-change room	Temporary quick-change rooms can be set at stage
	(must approved by Theatre Technical Department)



Wardrobe facilities

Artist's facilities

Washing machine and Dryer, Iron and Iron boards, steamer and sewing machine 2 washrooms with shower facilities, refrigerator and water dispenser, tables and chairs

FRONT OF HOUSE FACILITIES

Casual Bar at 1/F which accommodate for cocktail reception (max. 30 pax) Show relay at auditorium entrances in 1/F and 3/F for latecomers Tables (1.8L x 0.6D x 0.7H m) with red table cloths # Chairs # Movable display panels # Stanchions #

HKAC reserves the right to change the venue facilities without prior notice.

* Optional equipment for which an additional hiring charge will be applied.

These items are shared amongst several venues, the availability is subject to the requirements of the other venues